

## Carefree Satin

### Description

A water based low gloss acrylic/styrene polymer emulsion floor finish

### **Key properties**

Unique polymer technology from Johnson Diversey Optimal blend of polymers, waxes resins and film formation ingredients 18 % solids

Matting agents to provide low Satin like gloss.

### **Benefits**

- · Hard wearing durable finish ideal for low maintenance areas
- Produces a low gloss finish ideal for enhancing natural floors such as Stone and Linoleum

### Use instructions



Ensure old polish is removed Apply only to a clean dry floor Post Wet floor signs

Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out, the mop or applicator should be saturated but not dripping.

Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.

Allow 20 - 30 minutes drying time. Ensure  $1^{st}$  coat is completely dry before applying a second coat, at right angles to the first coat applying product up to the edges. If required apply a  $3^{rd}$  coat in a similar manner. Some floors such as stone, or worn porous linoleum/ vinyl will require sealing

Some floors such as stone, or worn porous linoleum/ vinyl will require sealing with Carefree Undercoat prior to application of Carefree Eternum

Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for Carefree Emulsion is Carefree Maintainer.

### **Technical data**

Appearance:	Milky emulsion
pH neat	8 - 9
pH Diluted	Not Applicable
S.G.	1.03
Visocity	5 cps

The above data is typical of normal production and should not be taken as a specification.

# F2f





### **Carefree Satin**

### Safe handling and storage information

Store in original closed containers away from extreme temperatures. Keep from freezing Do not use at temperatures below 10 deg C Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

### **Product compatibility**

Not suitable for unsealed wood. Some floors may require sealing prior to use e.g. Stone

### Available pack sizes

2 x 5 L

#### **Diversey Ltd**

Weston Favell Centre Northampton NN3 8PD Tel. 0800 525 525 www.diversey.com P91398GBEN-02