

# Carefree<sup>®</sup> Emulsion

## Floor Polish

### Description

Carefree Emulsion is a metallised dry bright floor polish which gives a long lasting gloss finish. Carefree Emulsion not only protects and extends the life of floors but also provides a safe high gloss finish which is easy to maintain and resistant to scuffing.

### Key properties

Unique triple polymer technology from Diversey Care 18 % solids Optimal blend of polymers, waxes resins and film formation ingredients. Provides a slip resistant finish.

### Benefits

- Produces a hard wearing durable floor finish
- Acts as a sacrificial wear layer for resilient and hard floor coverings
- Good level of gloss
- Excellent resistance to scuffs and marks

### Use instructions

1. Ensure old polish is removed
2. Apply only to a clean dry floor
3. Post wet floor signs
4. Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out, the mop or applicator should be saturated but not dripping

### Application

Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.


Allow 20 – 30 minutes drying time. Ensure 1st coat is completely dry before applying a second coat, at right angles to the first coat applying product up to the edges.

If required apply a 3rd coat in a similar manner.

Some floors such as stone, or worn porous/ vinyl will require sealing with Carefree Undercoat prior to application of Carefree Emulsion.

Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for Carefree Emulsion is Carefree Maintainer.

# F2d



© A.I.S.E.

# Carefree<sup>®</sup> Emulsion F2d

## Floor Polish

### Technical data

Appearance	Milky emulsion
pH value (neat)	8.0 – 9.0
pH diluted	Not applicable
S.G.	1.03
Viscosity	Water thin

*The above data is typical of normal production and should not be taken as a specification.*

### Safe handling and storage information

Store in original closed containers away from extreme temperatures. Keep from freezing. Do not use at temperatures below 10°C.

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

### Product compatibility

Suitable for use on vinyl, thermoplastic, rubber, linoleum, marble and terrazzo, it may also be used on sealed wood and cork floors.

### Available pack sizes

2 x 5 L