



FS1 Floor Polish

Stripper

NW: 11140

Product Uses For the stripping of metallised and non-metallised polish from linoleum, rubber, sealed wood, terrazzo and thermoplastic floors. Effective heavy duty formulation for the removal of impacted dirt from concrete and non-porous surfaces.

Directions POLISH STRIPPING: Polish stripping - dilute FS1 Floor Polish Stripper 1 part to 10 parts hot water. Allow to soak on floor for 10-15 minutes. Scrub thoroughly, preferably with a scrubbing machine fitted with a nylon scrubbing pad. Remove solution with a mop or suction drier. Rinse thoroughly and allow to dry before reapplying polish.

Composition	A fast acting formulation containing alkali builders, surfactants, penetrating agents, and sequestrants
Appearance	Clear Liquid
Colour	Blue
Cloud Point	38
Density	1.068
pH	>13.5
Stability	Two years in unopened containers

Environmental Profile



All surfactants contained in **Clean and Clever** products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.



Description of Product

No choking ammonia fumes. Quick removal of all emulsion and metallised polishes even those 'aged on'. Controlled foam for use with suction driers and combined machines. Modern chelating action "unlocks" metallised polishes.



Nationwide House, Peak Business Park,
Foxwood Road, Chesterfield,
Derbyshire S41 9RF
Tel: 0844 499 6380 Fax: 0844 499 6382
Email: sales@nationwide-hygiene.com