

Buckeye®

# JUGGERNAUT®

THE ULTIMATE COLD WATER FLOOR STRIPPER




## The Juggernaut Difference

**Juggernaut** The Ultimate Cold Water Floor Stripper is designed specifically to remove finish and seal from heavily burnished floors in one application! When your burnished, resilient tile, concrete, or masonry floors require a strip out, **Juggernaut** is the solution! **Juggernaut** is powerful without butyl, works in one application, and dilutes at 1:10 for less burnished finishes and 1:4 for tough jobs.

**Juggernaut** is designed to be used on all hard floor surfaces. **Juggernaut** has a mild and pleasant fragrance.

### Available Packaging



## FEATURES

- Faster acting
- Faster penetrating
- Liquefies heavily burnished finish and seal
- Contains Liquescent® technology for better performance and safety
- Butyl-free
- No added fragrance
- Less labor intensive
- Works in cold water
- Resists clogging of pads



# JUGGERNAUT®

THE ULTIMATE COLD WATER FLOOR STRIPPER

## DIRECTIONS FOR USE

(for use in COLD water)

### To Remove Non-Burnished Floor Finishes:

Use 12 oz./gallon water (100 ml/l), (1:10).

1. Apply **Juggernaut** solution liberally. Allow to stand 10 minutes. Keep floor wet during dwell time with stripper or water.
2. Machine scrub.
3. Pick up solution. Do not allow to dry on floor.
4. Rinse floor at least twice with cold water.
5. After floor is dry apply finish.

### To Remove Burnished Floor Finishes or Sealers:

Use 32 oz./gallon water (250 ml/l), (1:4).

1. Apply **Juggernaut** solution liberally. Allow to stand for 15 minutes. Follow steps 2-5 above. Keep floor wet during dwell time with stripper or water.

### Recommended for use with Buckeye's Action Control System® II.

For stripping non-burnished finish, use the GREEN Action Lock II Connector™.



For stripping burnished finish or seal, use the GRAY Action Lock II Connector.



## TECHNICAL SPECIFICATIONS

Total Actives	38.0 ± 0.2%
pH Concentrate	13.0 ± 0.2
pH (1:4)	12.3 ± 0.2
Weight/Gallon	8.76 lbs
Flash Point	None to Boiling
Color	Purple
Fragrance	Mild/Sweet
Hard Water Stability (1:10 with 350 ppm hard water)	Clear
Rinsing Properties	Excellent
Freeze-Thaw Stability	Unaffected by Freezing
Foaming Properties	Extremely Low

Product produced under one or more of the following U.S. patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341 and 5,849,682.

Canadian patents: 2,056,425; 2,080,352 and 2,057,027.

### BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com